

80mm

125mm

UltraFire®
UF01

LED







UltraFire®

LED

Technical Parameters

- Used XG2-3535 S3/S4 6000-6500K LED
- Adopt anti-reverse connection design to prevent the battery from being installed reversely and causing harm to the circuit
- Intelligent temperature control setting prevents the case temperature from being too high and affecting the comfort of use
- Made of aviation aluminum and has a hard anodized surface anti-wear treatment
- Compatible with a 1.5V/3.7V 14500 rechargeable lithium-ion battery, alkaline/Ni-MH battery
- Constant current circuit, constant brightness
- Memory function: turn the flashlight on for two seconds and then turn it off, turn on the flashlight again to work with the current memory position
- Tail tactical switch function
- Size: 93.5mm (length) * 19mm (diameter), net weight 38.5g (without battery)

UF01 parameters

	Battery	High	Low	Strobe
 Lumens	Alkaline / NiMH battery	60	10	60
	14500	500	50	500
 Endurance(Hour)	Alkaline / NiMH battery	2.5Hour	28Hour	/
	14500	1.0Hour	8.0Hour	/
 Light irradiation distance	Alkaline / NiMH battery	21	8	21
	14500	80	20	80
 LIGHT INTENSITY	Alkaline / NiMH battery	113	15	113
	14500	790	102	790



UN38.3
Made in China

